



## **DH2i DxEnterprise 20.0 Software: AWS AMI for Linux Quick Start Guide**

**DH2i Company**

Support: +1 (800) 380-5405 ext. 2

<https://dh2i.com/support/>

eFax: +1 970-295-4505

Email: [support@dh2i.com](mailto:support@dh2i.com)

<https://www.dh2i.com>

## AWS AMIs for Linux

This quick start guide describes how to configure DH2i's pay-as-you-go DxEnterprise Linux images available on AWS. Using this guide, the user will configure DxEnterprise on two servers (nodes) and join the second node into a cluster.

### Configure DxEnterprise

1. Use an SSH client to connect to the first server.
2. Set the hostname for the instance by running `sudo hostnamectl set-hostname <new_hostname>`.
3. Run the setup.sh script to configure DxEnterprise and activate the server.

#### Syntax

```
sudo bash /opt/dh2i/bin/setup.sh
```

4. Set the cluster passkey using the command `sudo dxcli cluster-set-secret`.

#### Syntax

```
dxcli cluster-set-secret
```

#### Parameters

Interactive only.

#### Example

```
dxcli cluster-set-secret
```

5. OPTIONAL: DxEnterprise can utilize NAT matchmaking to easily connect servers across the internet. Use the command `sudo dxcli set-otpk` to set a One-Time PassKey for the cluster. The passkey expires one hour after creation by default.

#### Syntax

```
dxcli set-otpk [ttl] [otpk]
```

#### Parameters

Name	Description	Required
ttl	The time the key will expire.	False
otpk	The One-Time PassKey in base64.	False

#### Example

```
dxcli set-otpk
```

### Setup Second Node and Join to Cluster

1. Use an SSH client to connect to the second server.
2. Complete steps 2-3 of the [Configure DxEnterprise](#) section for the second node.
3. Join the second node to the cluster using `sudo dxcli join-cluster` and follow the prompts.

- If an OTPK was *not* set for the cluster, select **N** when prompted to join via NAT proxy. Enter the IP address and cluster passkey of the first server to join the cluster.
- If an OTPK was set for the cluster, select **Y** when prompted to join via NAT proxy. Enter the OTPK to join the cluster.

**Syntax**

```
dxcli join-cluster
```

**Parameters**

Interactive only.

**Example**

```
dxcli join-cluster
```

4. Read the following docs for more information about configuring the cluster:
  - [AWS Load Balancer Quick Start Guide](#)
  - [MSSQL Availability Groups with DxCLI Quick Start Guide](#)
  - [MSSQL HA Instances on Linux Quick Start Guide](#)

## References

- [DxEnterprise Admin Guide](#)
- [DxEnterprise DxCli Guide](#)
- [DH2i Support Portal](#)