



DH2i DxOdyssey 19.5 Software: RHEL Quickstart Guide

DH2i Company

Support: +1 (800) 380-5405 ext 2

support.dh2i.com

eFax: +1 970-295-4505

support@dh2i.com

www.dh2i.com

Install and configure Redhat Enterprise Linux / CentOS - 7.3

Install updates

- `sudo yum update`

Set host resolution for all gateways and tunnel groups

- `sudo nano /etc/hosts`

Ensure hostname is set and unique

- `hostname`
- `sudo hostnamectl set-hostname <name>`

(restart required if changed)

Install .Net Core (via RHEL subscription)

- `subscription-manager repos --enable=rhel-7-server-dotnet-rpms`
- `yum install scl-utils`
- `yum install rh-dotnet31-dotnet-runtime-3.1`
- `scl enable rh-dotnet31 bash`

Install .Net Core (via Centos repository)

- `sudo rpm -Uvh https://packages.microsoft.com/config/centos/7/packages-microsoft-prod.rpm`
- `sudo yum install dotnet-runtime-3.1`

Install applications

Install DxOdyssey

- Place a copy of the DxOdyssey RPM in a local directory
- `sudo rpm -Uvh dxodyssey-<version>.x86_64.rpm`

Activate server license (First gateway installation)

- `sudo dxcli activate-server AAAA-BBBB-CCCC-DDDD`

Set gateway group (cluster) passkey (First gateway installation)

- `sudo dxcli gateway-group-set-secret`

Set OTPK (First gateway installation)

- `sudo dxcli set-otpk`

Join existing gateway group (cluster) (After initial gateway installed)

- `sudo dxcli join-gateway-group`

References

- [DH2i Support Portal](#)